







On Site Spill Containment

This specialized berm is compact, lightweight, and portable - it features struts in sleeves along the sidewall.

## Design Features:

- ▶ Fully welded construction made from 28 oz/yd2 (950 gsm) COPOLYMER 2000 fabric, black
- ▶ Berm sidewall struts are permanently attached, no parts to misplace or lose
- ▶ Compact design (12"& 15" sidewalls up for easy stores (12" trucks / hazmat vehicles

▶ 12 inch high walls provide high storage volume (up to triple capacity of similar footprint foam side wall berms)

Part Number L x W x H Shipping Weight Capacity (ft x ft x ft) 680 L (180 USG) 13 kg (29 lbs) PSP200-4020 4 x 6 x 1 1,020 L (270 USG) 16 kg (35 lbs) PSP200-4021 6 x 6 x 1 PSP200-4022 10 x 10 x 1 2,830 L (750 USG) 29 kg (63 lbs) 140 kg (309 lbs) PSP200-4023 12 x 60 x 1 20,380 L (5,385 USG) 21,235 L (5,610 USG) 127 kg (278 lbs) PSP200-4024 15 x 50 x 1 28,030 L (7,405 USG) 162 kg (357 lbs) PSP200-4025 15 x 66 x 1














# **ACCESSORIES** ~

Spill containment protection applications are often unique – aside from offering a complete range of custom berm sizes and configurations, we can build to meet your specific requirements.

In addition, we offer accessories which include:



Track Belts Track Belts – Protect berm from drive over wear and tear.



**Ground Sheets** Use these to protect your berm from rocks, debris, and other objects.



Hose Stands Hoses stands – keep hoses from damaging sidewalls and reducing your berm containment capacity.



Self Bailers Passively filters hydrocarbons while allowing accumulated rainwater to discharge. Simple installation.

### Represented By



### Head Office & Warehouse

135-12320 Vulcan Way, Richmond, BC, Canada, V6V 1J8

Office Tel: 604-244-7745 Office Fax: 604-247-2298 Toll Free / Emergency: 1-855-269-7745 (1-855-ANY-SPILL)



**CONTAINMENT PRODUCTS** 

# **SECONDARY CONTAINMENT**















noose From



Custom Silk

These collapsible secondary containment berms can be used to contain spills and leaks from vehicles, machinery, tanks, drums and other industrial equipment.

### Design Features:

- ▶ RF welded construction made from your choice of three (3) heavy duty industrial fabrics
- > 22 oz/yd2 (750 gsm) PVC coated polyester, yellow
- > 28 oz/yd2 (950 gsm) PVC coated polyester, orange
- > 30 oz/yd2 (1020 gsm) Chemical & Hydrocarbon Resistant polyester, black
- ▶ Lightweight, flexible, compact folds up for storage and easily portable for transport
- ▶ Simple and easy to clean and maintain, re-usable No set up – unfold and use immediately!

### Colours / Material

- Yellow 22 oz PVC
- Orange 28 oz PVC
- Black 30 oz Chem Resistant / XR5

lkscreening Available	3 Fabric Options To Cho

Part Number	L x W x H (in x in x in)	Capacity (90%)	Shipping Weight
PSP200-1007	24 x 24 x 4	34 L (9 USG)	1.1 kg (2.4 lbs)
PSP200-1008	24 x 24 x 4	34 L (9 USG)	1.4 kg (3.0 lbs)
PSP200-1009	24 x 24 x 4	34 L (9 USG)	1.5 kg (3.2 lbs)
PSP200-1010	24 x 24 x 6	51 L (14 USG)	1.3 kg (2.9 lbs)
PSP200-1011	24 x 24 x 6	51 L (14 USG)	1.6 kg (3.6 lbs)
PSP200-1012	24 x 24 x 6	51 L (14 USG)	1.7 kg (3.8 lbs)
PSP200-1013	36 x 36 x 4	77 L (20 USG)	1.7 kg (3.8 lbs)
PSP200-1014	36 x 36 x 4	77 L (20 USG)	2.2 kg (4.8 lbs)
PSP200-1015	36 x 36 x 4	77 L (20 USG)	2.3 kg (5.1 lbs)
PSP200-1016	36 x 36 x 6	115 L (31 USG)	2.0 kg (4.4 lbs)
PSP200-1017	36 x 36 x 6	115 L (31 USG)	2.5 kg (5.5 lbs)
PSP200-1018	36 x 36 x 6	115 L (31 USG)	2.7 kg (5.9 lbs)
PSP200-1019	48 x 48 x 4	136 L (36 USG)	2.5 kg (5.5 lbs)
PSP200-1020	48 x 48 x 4	136 L (36 USG)	3.2 kg (7.0 lbs)
PSP200-1021	48 x 48 x 4	136 L (36 USG)	3.4 kg (7.4 lbs)
PSP200-1022	48 x 48 x 6	204 L (54 USG)	2.9 kg (6.4 lbs)
PSP200-1023	48 x 48 x 6	204 L (54 USG)	3.6 kg (7.9 lbs)
_			

# PSP200-1024 48 x 48 x 6 204 L (54 USG) 3.8 kg (8.4 lbs)





vehicles or machinery.

Design Features:

Colours / Material

■ Black 30 oz Chem Resistant / XR5

fabric, black

These L-Rod secondary containment berms are fully

berms, but are easily folded to allow for entry/exit of

▶ RF welded construction made from 30 oz/yd2

collapsible, and can be rapidly deployed. Aluminum L-rods

(1020 gsm) Chemical & Hydrocarbon Resistant polyester

▶ Aluminum L-Rods used to support the berm walls, but

easily foldable for entry / exit and for storage

▶ Simple and easy to clean and maintain, re-usable

are used at regular intervals to support the walls of the



6, 12, or 15 Inch High Berm Sidewalls



Rapidly Set Up With No Tools

Part Number	L x W x H (ft x ft x in)	Capacity (90%) Ship	pping Weight
PSP200-3001	10 x 10 x 6	1275 L (340 USG)	15 kg (33 lbs)
PSP200-3002	10 x 15 x 6	1915 L (510 USG)	21 kg (46 lbs)
PSP200-3003	8 x 12 x 12	2450 L (650 USG)	19 kg (41 lbs)
PSP200-3004	8 x 8 x 12	1630 L (430 USG)	14 kg (31 lbs)
PSP200-3005	8′ x 10 x 12	2040 L (540 USG)	16 kg (36 lbs)
PSP200-3006	10 x 10 x 12	2550 L (675 USG)	19 kg (42 lbs)
PSP200-3007	10 x 15 x 12	3825 L (1010 USG)	26 kg (57 lbs)
PSP200-3008	10 x 20 x 12	5100 L (1350 USG)	33 kg (73 lbs)
PSP200-3009	15 x 15 x 12	5740 L (1520 USG)	35 kg (78 lbs)
PSP200-3010	20 x 20 x 12	10200 L (2695 USG)	57 kg (125 lbs)
PSP200-3011	8 x 8 x 15	2040 L (540 USG)	16 kg (34 lbs)
PSP200-3012	8 x 10 x 15	2550 L (675 USG)	18 kg (40 lbs)
PSP200-3013	8 x 15 x 15	3825 L (1010 USG)	25 kg (54 lbs)
PSP200-3014	10 x 10 x 15	3190 L (845 USG)	21 kg (47 lbs)
PSP200-3015	10 x 15 x 15	4780 L (1265 USG)	29 kg (63 lbs)
PSP200-3016	10 x 20 x 15	6375 L (1685 USG)	36 kg (79 lbs)
PSP200-3017	15 x 20 x 15	9565 L (2530 USG)	48 kg (106 lbs)
PSP200-3018	20 x 20 x 15	12750 L (3370 USG)	60 kg (133 lbs)

















Drive In/Out, No Set Up



Foam Ring Rises With Liquid Level



Simple And Easy To Deploy

This specialized berm allows for easy entry and exit of vehicles or equipment. Sidewalls remain down during normal operations, loading and unloading. Vehicles and equipment can drive in and out with no set-up or takedown required. In the case of a spill, the foam ring around the top perimeter of the berm rises with the level of the spilled liquid

### Design Features:



- ▶ Lays flat until spill occurs then foam ring around top perimeter will rise with fluid level
- ▶ No tripping hazards, simple and easy to deploy, clean and maintain
- ▶ 12 inch high walls provide high storage volume (up to triple capacity of similar footprint foam side wall berms)

### Colours / Material

■ Black 28 oz Copolymer 2000

Part Number	L x W x H (ft x ft x ft)	Capacity	Shipping Weight
PSP200-4014	4 x 6 x 1	680 L (180 USG)	13 kg (29 lbs)
PSP200-4015	6 x 6 x 1	1,020 L (270 USG)	16 kg (35 lbs)
PSP200-4016	10 x 10 x 1	2,830 L (750 USG)	29 kg (63 lbs)
PSP200-4017	12 x 26 x 1	8,830 L (2,335 USG	68 kg (149 lbs)
PSP200-4018	15 x 50 x 1	21,235 L (5,610 US	GG) 127 kg (278 lbs)
PSP200-4019	15 x 66 x 1	28,030 L (7,405 US	G) 162 kg (357 lbs)









